

µC Based Temperature Controller-On/off

Single Display



- WTC-1201-OF....Size: 96(w)x96(h)x65(d) mm
- WTC-1001-OF....Size: 96(w)x48(h)x110(d) mm
- WTC-1101-OF....Size: 72(w)x72(h)x110(d) mm
- WTC-1301-OF....Size: 48(w)x48(h)x85(d) mm

- microcontroller based,
- Four digit display
- Supply 220 VAC
- Input J, K or RTD selection
- Output: 1. Relay Contact or SSR, 2. Alarm contact or Buzzer (Optional)
- On/Off Control selection
- Heating or Cooling Application selection
- Range: J type 0-750°C,
K type 0-1200°C,
RTD.1 type -50.0 to 400.0°C,
RTD type 0 to 400°C
- Accuracy of 0.5% of full scale
- Temperature As per range adjustable in set mode.
- Alarm 0.0 to 25.0 or 0 to 250 as per range adjustable
- Hysteresis 0.2 or 2 to 25.0°C or 25°C adjustable as per range selection for RTD
- Hysteresis 2 to 250°C adjustable as per range selection for J & K Type
- Delay 0 to 250 second adjustable for cooling control
- OPEN display if Sensor break & -REV display if connections reverse.
- Relay trip if sensor breaks, connection open or connection reverse.
- Calibration Error correction by front key switch (No preset setting)
- Configure link @ Back terminal to avoid unauthentic entry.

WAVE INSTRUMENTS LLP

L-45/9, Phase-3, Opp. Mazda Ltd., GIDC Naroda, Ahmedabad -382330, Gujarat – INDIA

☎ +91- 9722003425, ☎ +91-79-40043425, 📞 +91-7043003425.

Email: waveinstruments@gmail.com, Website: <http://www.wavetronics.co.in>